

## Damask Steel

## Damask Steel Black

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	24N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	300%
Self-Healing	PASS	60° Surface Gloss	37
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

\*The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us. \*The above data is used as a reference for material selection, but does not constitute a guarantee.

\*The company has the right to modify the relevant technical data without prior notice.





## Damask Steel

## Damask Steel Clear

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	11N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	320%
Self-Healing	PASS	60° Surface Gloss	54
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

\*The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us. \*The above data is used as a reference for material selection, but does not constitute a guarantee.

\*The company has the right to modify the relevant technical data without prior notice.









