

Gloss Colored Series

Gloss Blue&Purple

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	23N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	292%
Self-Healing	PASS	60° Surface Gloss	94
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

^{*}The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

^{*}The company has the right to modify the relevant technical data without prior notice.











^{*}The above data is used as a reference for material selection, but does not constitute a guarantee.



Gloss Colored Series

Gloss Gold&Green

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	25N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	301%
Self-Healing	PASS	60° Surface Gloss	95
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

^{*}The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

^{*}The company has the right to modify the relevant technical data without prior notice.











^{*}The above data is used as a reference for material selection, but does not constitute a guarantee.



Gloss Colored Series

Gloss Pink&Gold

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	24N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	312%
Self-Healing	PASS	60° Surface Gloss	97
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

^{*}The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

^{*}The company has the right to modify the relevant technical data without prior notice.











^{*}The above data is used as a reference for material selection, but does not constitute a guarantee.