

Satin Colored Series

Satin Blue&Purple

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	12N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	360%
Self-Healing	PASS	60° Surface Gloss	30
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

^{*}The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

^{*}The company has the right to modify the relevant technical data without prior notice.











^{*}The above data is used as a reference for material selection, but does not constitute a guarantee.



Satin Colored Series

Satin Gold&Green

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	 12N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	353%
Self-Healing	PASS	60° Surface Gloss	30
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	l 10 Years	Anti Rock Chips Test	PASS

^{*}The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

 $^{^{*}}$ The company has the right to modify the relevant technical data without prior notice.











^{*}The above data is used as a reference for material selection, but does not constitute a guarantee.



Satin Colored Series

Satin Pink&Gold

CATEGORY	VALUE	CATEGORY	VALUE
Top Coating	PLATICOAT™	Temperature Resistance	-40°C-120°C -40°F-248°F
Base Film Type	Polycaprolactone Aliphatic TPU	Initial Peel Adhesion	11N/in
Adhesive Type	Repositionable Acrylic PSA	Elongation At Break	360%
Self-Healing	PASS	60° Surface Gloss	31
Film Thickness	8mil	UV Test	5000 Hours Pass
Film Specification	60in × 50ft	Chemical Resistance	No Harm
Warranty	10 Years	Anti Rock Chips Test	PASS

^{*}The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

^{*}The company has the right to modify the relevant technical data without prior notice.











^{*}The above data is used as a reference for material selection, but does not constitute a guarantee.